



## Technical data sheet

### Rivo drainage grate



### Manufacturer

Richard Brink GmbH & Co KG  
Metal goods manufacture and distribution  
Görlitzer Str. 1  
33758 Schloß Holte-Stukenbrock  
Phone: 0049 (0)5207 9504-0  
Fax: 0049 (0)5207 9504-20

Status: 06/20



## Product description

Rivo drainage gratings are cover gratings with perforations.

The grates are available in stainless steel (V2A).

## Load class

The drainage gratings are designed in accordance with load class A15 (*walkable*).

## Grate dimensions

<u>Inlet width</u>	<u>Height</u>	<u>Recesses</u>
100 mm	20 mm	37 %
140 mm	20 mm	37 %
160 mm	20 mm	37 %

The standard grating length is 1,000 mm, due to the design no special dimensions are possible.

## Slip resistance

The slip resistance of the grates corresponds to slip rating class R10.

## Clear mesh size

The requirements of the German Social Accident Insurance (DGUV-Information 208-007 Gratings - Selection and Operation) are met. The clear mesh width must not exceed 10 mm to ensure safe walking and driving on.



## **Materials used**

We use only European material from Germany, Sweden, France and Italy for our grates.

## **Material specification**

Stainless steel V2A (1.4301)

The material thickness is 3.0 mm

## **Accessories**

- corners, factory prepared

## **Processing and care instructions**

The grates must not be cleaned with strong acids or bases, but by hand with a broom or, if necessary, with a high-pressure cleaner.

Further installation & usage instructions as well as information on the material can be found at:  
<https://www.richard-brink.de/downloads/gesamtuebersicht.html>