



## Technical data sheet

# Drainage longitudinal grating Staccato



### Manufacturer

Richard Brink GmbH & Co KG  
Metal goods manufacture and distribution  
Görlitzer Str. 1  
33758 Schloß Holte-Stukenbrock  
Phone: 0049 (0)5207 9504-0  
Fax: 0049 (0)5207 9504-20

Status: 02/22



## Product description

The Staccato longitudinal drainage grating is a box gutter cover grating.

The grate is made of stainless steel (V2A).

## Load class

The Staccato longitudinal drainage grating is designed in accordance with load class A15 (*walkable*).

On request, the grating is also available for heavy-duty use in accordance with load class D400 (*trafficable*).

## Dimensions

<u>Inlet width</u>	<u>Height</u>	<u>Bar thickness</u>
100 mm	20 mm	20 x 3 mm
140 mm	20 mm	20 x 3 mm
200 mm	20 mm	20 x 3 mm

The standard grating length is 1,000 mm in each case.

Special sizes are possible on customer request.

## Inlet cross-sections of the grates

Inlet width 100 mm:	715 cm <sup>2</sup> /m
Inlet width 140 mm:	1.051cm <sup>2</sup> /m
Inlet width 200 mm:	1.492 cm <sup>2</sup> /m

## Slip resistance

The slip resistance of the grates corresponds to slip rating class R10.



## **Clear mesh size**

The requirements of the German Social Accident Insurance (*DGVU-Information 208-007 Gratings - Selection and Operation*) are met. The clear mesh width must not exceed 10 mm to ensure safe walking and driving on.

## **Materials used**

We use only European material from Germany, Sweden, France and Italy for our grates.

## **Material specification**

Stainless steel V2A (1.4301)

## **Accessories**

- Corners, factory prepared
- Stainless steel grate locks

## **Processing and care instructions**

The grates can be cut to size. However, it must be ensured that the cutting medium (e.g. *saw blade, cutting disc, etc.*) is absolutely clean or does not contain any components of other metals, as otherwise corrosion may occur.

Dust particles of other metals or general cutting of components with flying sparks on the product are generally to be avoided. If dust particles or soiling of other metals are present, these must be removed immediately with appropriate cleaning agents.

The grates must not be cleaned with strong acids or bases, but by hand with a broom or, if necessary, with a high-pressure cleaner.

Further installation & usage instructions as well as information on the material can be found at:  
<https://www.richard-brink.de/downloads/gesamtuebersicht.html>