



Technical data sheet

Shuttering frame RB-SR



Manufacturer

Richard Brink GmbH & Co KG
Metal goods manufacture and distribution
Görlitzer Str. 1
33758 Schloß Holte-Stukenbrock
Phone: 0049 (0)5207 9504-0
Fax: 0049 (0)5207 9504-20



Product description

Simple handling instead of time-consuming work steps. When building a new chimney or completely renovating a dilapidated chimney head, you can rely on our shuttering frames, which enable installation in just a few steps: first, the customised shuttering frame and the expansion joint plate are placed on the chimney head. The components then prevent concrete from running into the cladding and the chimney flue. The formwork frame is then filled with concrete.

Dimensions

Shuttering frames are manufactured according to your dimensions. The dimensions required for this are the external dimensions of the chimney including cladding, if present.

Material

Stainless steel (V2A) 1.0 mm, bright or painted black

Processing and care instructions

Care should always be taken when processing the shuttering frames.

Dust particles of other metals or general cutting of components with flying sparks on the product should be avoided, as they are very sensitive. If dust particles or soiling of other metals are present, these must be removed immediately using appropriate cleaning agents.

Further installation and usage instructions as well as information on the material can be found at: <https://www.richard-brink.de/en/downloads/overview.html>